

Q.HOME COMBINER

Q.HOME COMBINER 80 G1

Q.HOME COMBINER

The Q.HOME SMART Residential Energy Solution Combiner Box



Flexible

- Network connectivity with Wi-Fi, Ethernet or Cellular



Consolidated

- Supports 64A input of Solar or Solar + Storage
- Supports up to 144 AC Modules (using external subpanel)



Robust

- NRTL-certified NEMA type 3R enclosure rated for outdoor installation



Streamlined

- Pre-installed revenue grade production meter
- 2 slim clamp CTs provided for consumption metering



Reliable

- 5-year warranty
- Automatic firmware updates



Complete

- Part of Qcells' complete Q.HOME SMART solution offering
- One brand. One warrantor.

■ Description

Q.HOME COMBINER 80 G1 consolidates up to 4 PV strings with a maximum of 44 AC Modules connected into a single enclosure. This enables a smooth interconnection across Q.HOME SMART products while ensuring easy and fast installations. Save time and costs by incorporating this user-friendly combiner box, optimally designed for residential applications.

■ Technical Specification

GENERAL PRODUCT INFORMATION		Q.HOME COMBINER 80 G1
Manufacturer		Hanwha Solutions Corporation
Product Warranty		5 years
Country of Manufacture		Vietnam

ACCESSORIES AND REPLACEMENT PARTS	
Supported AC Modules (Microinverter included)	Q.TRON BLK M-G2+/AC, Q.TRON BLK M-G2.H1+/AC
Cellular Modem (CELLULAR-MT-MODEM-CAT4-TN5)	4G based LTE-CAT4 (+5year data plan included)
Wi-Fi Dongle (WIFI-HQ-DG-USB)	FCC Part 15 Subpart C/2412.0 to 2462.0MHz **
Circuit Breakers	Supports Eaton BR210, BR215*, BR220, BR230, BR240, BR250, and BR260 circuit breakers
Consumption Monitoring CT (CT-JS-CLAMP-200A-5.2m)	A pair of 200A clamp type current transformers (accuracy ±0.5%) **

* pre-assembled / ** included in the package
(Others are not included, need to be ordered separately)

ELECTRICAL SPECIFICATIONS	
System Voltage	[V] 120/240 VAC, 60 Hz
Eaton BR Series Busbar Rating	[A] 125
Max. Continuous Current Rating (input from PV / storage)	[A] 64
Branch Circuits (Solar or Solar + Storage)	[pcs] Up to four 2-pole Eaton BR series Distributed Generation (DG) breakers only (not included)
Max. Total Branch Circuit Breaker Rating (input)	[A] 80 A of distributed generation / 95 A with Gateway breaker included
Gateway Circuit Breaker	[A] 15 A rating Eaton BR215 included
Consumption Monitoring	[A] Metering with a pair of 200 A slim clamp current transformers (accuracy ±2.0 %)
Production Metering	[A] Metering with 200A solid core current transformer, pre-wired to Gateway (accuracy ±0.5 %)

MECHANICAL DATA	
Max. AC Module Connection Q'ty	[pcs] <ul style="list-style-type: none">Up to 44 AC Modules in 1 combiner (11 in series × 4 strings)Up to 144 AC Modules using 1 combiner with external subpanel
Dimensions (W × H × D)	[inch] 14.6 × 19.3 × 6.3 / height is 21.7 with mounting brackets (37.0 × 49.0 × 16.0 cm / height is 55.1cm with mounting brackets)
Weights (without connection cables)	[lb] 11.5 (5.2 kg)
Operating Temperature Range	[°F] -40 to 140 (-40 to 60 °C)
Storage Temperature Range	[°F] -40 to 140 (-40 to 60 °C)
Enclosure Environmental Rating	Outdoor, NRTL-certified, NEMA type 3R
Wire Sizes	<ul style="list-style-type: none">20 A breaker inputs: 12 to 8 AWG copper conductorsMain lug combined output: 10 to 2/0 AWG copper conductorsNeutral and ground: 8 to 6 copper conductorsAlways follow local code requirements for conductor sizing
Cooling	Natural convection
Altitude	[ft] Up to 6,561 (2,000 m)

INTERNET CONNECTION OPTIONS	
Wi-Fi	IEEE 802.11b/g/n
Cellular	CELLMODEM-CAT4 (4G based LTE-CAT4)
Ethernet	Optional, IEEE 802.3, CAT5E (or CAT6) STP Ethernet cable

COMPLIANCE	
AC Combiner	<ul style="list-style-type: none">UL 1741, CSA C22.2 No.107FCC Part 15.BANSI C 12.20 accuracy class 0.5 (production meter)NEMA type 3RIEEE 2030.5 / CSIP Compliant
Monitoring Board	UL 61010-1 / UL 61010-2-030 CSA 22.2 No. 61010-1-12 / CSA 22.2 No. 61010-2-030
CT Sensor	UL 2808 (XOBA)

■ Qualifications and Certificates




■ Accessories

Parts Included in the Package



WIFI-HQ-DG-USB Wi-Fi dongle with 2.4GHz bandwidth

FCC ID: OZ5C307-HW-WF



CT-JS-CLAMP-200A-5.2m A slim clamp type consumption CT with ±0.5% accuracy (5.2m, 20AWG)

UL 2808(XOBA) E498920

Additional Parts (Not Included in the Package)




CT-HQ-SOLID-200A-2m A solid core production CT with ±0.1% accuracy (2m, 18AWG)
■ Required for >44 AC Module solution

UL 2808(XOBA) E535456



CT-JS-CLAMP-200A-25m A slim clamp type consumption CT with ±0.5% accuracy (25m, 20AWG)

UL 2808(XOBA) E498920



CELLULAR-MT-MODEM-CAT4-TN5 Cellular modem with 5 year data plan included

UL 62368-1 E150299



CELLULAR-TN-DP-5Y 5 year data plan extension

